


DD2001

MONITOR/FR-1 /230VAC

Evaluation systems, power supplies

 replaced by: DD2503
 Article available until 31 March 2014


- 1: LCD display; 7/14-segment
 2: Programming buttons
 3: LEDs

Made in Germany


Product characteristics

MONITOR

FR-1

Housing for DIN rail mounting

2 relay outputs

2 transistor outputs

Analogue output

0/4...20 mA

programmable

Test function without external frequency

Key function

Application

Application	single pulse evaluation system with μ processor for frequency; rotational speed; speed and machine cycles
Switching function	2 switch points for monitoring overspeed/underspeed and acceptable range

Electrical data

Nominal voltage	[V]	230 AC (50...60 Hz) / 24 DC
Voltage tolerance	[%]	± 10
Power consumption	[VA]	5 (3 W)

Inputs

Inputs	pnp/npn; NAMUR (24 V) auxiliary supply: typ. 24 V DC / 15 mA; short-circuit protected threshold pnp: > 12 V on; < 5 V off threshold npn: > 15 V off; < 8 V on input frequency (max): 5 kHz (corresponds to min. pulse length / space 0.1 ms)
--------	--

Outputs

Relay	
Contact rating	8 A (1250 VA / 250 V AC)
Transistor	
Transistor outputs	pnp; external supply switching voltage/current: 24 V DC / max. 15 mA; short-circuit protected



DD2001

MONITOR/FR-1 /230VAC

Evaluation systems, power supplies

analogue

Analogue output	0/4...20 mA
Max. load [Ω]	500
	limitation: 20.5 mA; accuracy: 1 % (of the final value)

Measuring / setting range

Setting range [pulses/min.]	1...60000 (0.1...1000 Hz)
-----------------------------	---------------------------

Accuracy / deviations

Measuring error [% of the final value]	< 1
--	-----

Environment

Ambient temperature [°C]	-20...60
Storage temperature [°C]	-25...80
Max. relative air humidity [%]	75 (35°C)
Protection housing / terminals	IP 50 / IP 20

Tests / approvals

EMC	EN 61010 : 2001
	EMC 89/336/EEC
	EN 61000-6-3 : 2007
	EN 61000-6-2 : 2005

Mechanical data

Housing materials	plastics
Weight [kg]	0.365

Displays / operating elements

Input pulses LED	yellow
Output status indication LED	green (lights when the relay is energised / the transistor is closed)
Function display LED	LCD display; 7/14-segment

Electrical connection

Connection	dual-chamber terminals 2 x 2.5 mm²
------------	------------------------------------

Wiring

- 1: DC Supply voltage (L-)
- 2: DC Supply voltage (L+)
- 3: supply transistor outputs (L+)
- 4: sensor signal pnp
- 5: DC Sensor supply (L+)
- 6: DC Sensor supply (L-)
- 7: AC Supply voltage
- 8: AC Supply voltage
- 9: n.c.
- 10: sensor signal npn
- 11: n.c.
- 12: n.c.
- 13: Relay 1 (common)
- 14: Relay 1 (normally open)
- 15: Relay 1 (normally closed)
- 16: transistor output 1 pnp
- 17: Reset 1 pnp
- 18: Reset 2 pnp
- 19: Relay 2 (common)
- 20: Relay 2 (normally open)
- 21: Relay 2 (normally closed)
- 22: analogue output (+)
- 23: analogue output (-)
- 24: transistor output 2 pnp

Remarks

**DD2001**

MONITOR/FR-1 /230VAC

Evaluation systems, power supplies

Remarks	overvoltage category II; degree of soiling 2
Pack quantity [piece]	1

ifm electronic gmbh • Friedrichstraße 1 • 45128 Essen — We reserve the right to make technical alterations without prior notice. — GB — DD2001 — 27.03.2013

replaced by: DD2503
Article available until 31 March 2014