

Configuration summary

| Mat. no. | Description Order code | Quantity | Unit |
|----------|---|----------|------|
| 71086210 | Cerabar M PMP55 PMP55-AA22QA1MGBTRJA4A | 1 | ST |

| | | | |
|-----|----------------------------|-----|--|
| 010 | Approval: | AA | Non-hazardous area |
| 020 | Output: | 2 | 4-20mA HART |
| 030 | Display, Operation: | 2 | W/o LCD, push button on electronics |
| 040 | Housing: | Q | F15 stainless steel hygiene |
| 050 | Electrical Connection: | A | Gland M20, IP66/68 NEMA4X/6P |
| 070 | Sensor Range: | 1M | 4bar/400kPa/60psi gauge, 40mH2O/133ftH2O/1600inH2O overload: 28bar/2.8MPa/420psi |
| 080 | Reference Accuracy: | G | Standard |
| 090 | Calibration; Unit: | B | Sensor range; mbar/bar |
| 110 | Process Connection: | TRJ | Varivent N tube DN40-162 PN40, 316L, EHEDG, 3A |
| 170 | Membrane Material: | A | 316L |
| 180 | Fill Fluid: | 4 | Vegetable oil, FDA |
| 200 | Diaphragm Seal Connection: | A | Direct |