



**Electric Automation**  
Automation specialists

Reference: PDQ22-FBP  
Code: 1SAJ240200R0050

PROFIBUS DP-V0/V1 FieldBusPlug Quad

Buy it at Electric Automation Network



Ready-made Profibus DP/V1 fieldbus interface for four devices. Applicable with all FBP motor starters and other terminal devices. Degree of protection IP65, diagnostic LED

### Ordering

EAN:	4013614380136
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85176200

### Dimensions

Product Net Weight:	443 g
---------------------	-------

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	112 mm
Package Level 1 Height:	67 mm
Package Level 1 Length:	26 mm
Package Level 1 Gross Weight:	0.443 kg

### Environmental

RoHS Status:	No declaration needed
--------------	-----------------------

## Additional Information

Degree of Protection:	IP65
Fieldbus Interface Type:	PROFIBUS
IIT Publishing Status:	Level 0 - Information enabled
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Mounting Type:	Single Mounting
Product Main Type:	PDQ22-FBP
Product Name:	Cable
Rated Control Supply Voltage (U <sub>s</sub> ):	24 V DC

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CDC192009D0201
Declaration of Conformity - CE:	1SAD938500-0096
RoHS Information:	1SAA962001-4401

## Classifications

eClass:	7.0 27242608
E-nummer:	4517257
ETIM 4:	EC001604 - Fieldbus, decentr. periphery - communication module
ETIM 5:	EC001604 - Fieldbus, decentr. periphery - communication module
Object Classification Code:	K
UNSPSC:	39120000