

SIMATIC S7-400, CPU 412-2 CENTRAL PROCESSING UNIT WITH:
256 KB WORKING MEMORY, (128 KB CODE, 128 KB DATA), 1.
INTERFACE MPI/DP 12 MBIT/S, 2. INTERFACE PROFIBUS DP

General information

Firmware version	V4.0
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.2 SP1 HF3 or higher with HW update

CiR – Configuration in RUN

CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	200 μ s

Supply voltage

Rated value (DC)	
<ul style="list-style-type: none"> 24 V DC 	Yes

Input current

from backplane bus 5 V DC, typ.	1 A
from backplane bus 5 V DC, max.	1.2 A
from backplane bus 24 V DC, max.	Total current consumption of the components connected to the MPI/DP interfaces, but no more than 150 mA per interface

Power loss

Power loss, typ.	4.5 W
------------------	-------

Memory

Work memory	
<ul style="list-style-type: none"> integrated (for program) 	128 kbyte
<ul style="list-style-type: none"> integrated (for data) 	128 kbyte
<ul style="list-style-type: none"> expandable 	No
Load memory	
<ul style="list-style-type: none"> expandable FEPR0M 	Yes; with Memory Card (FLASH)
<ul style="list-style-type: none"> expandable FEPR0M, max. 	64 Mbyte
<ul style="list-style-type: none"> integrated RAM, max. 	256 kbyte
<ul style="list-style-type: none"> expandable RAM 	Yes; with Memory Card (RAM)
<ul style="list-style-type: none"> expandable RAM, max. 	16 Mbyte
Backup	
<ul style="list-style-type: none"> present 	Yes
<ul style="list-style-type: none"> with battery 	Yes; all data
<ul style="list-style-type: none"> without battery 	No

Battery

Backup battery

- | | |
|---|-------------------|
| • Backup current, typ. | 350 μ A |
| • Backup current, max. | 890 μ A |
| • Backup time, max. | 226 d |
| • Feeding of external backup voltage to CPU | 5 V DC to 15 V DC |

CPU processing times

- | | |
|-------------------------------------|-------------|
| for bit operations, typ. | 0.1 μ s |
| for word operations, typ. | 0.1 μ s |
| for fixed point arithmetic, typ. | 0.1 μ s |
| for floating point arithmetic, typ. | 0.3 μ s |

CPU-blocks

DB

- | | |
|----------------|--------------------|
| • Number, max. | 512; DB 0 reserved |
| • Size, max. | 64 kbyte |

FB

- | | |
|----------------|----------|
| • Number, max. | 256 |
| • Size, max. | 64 kbyte |

FC

- | | |
|----------------|----------|
| • Number, max. | 256 |
| • Size, max. | 64 kbyte |

OB

- | | |
|----------------------------------|----------------------|
| • Number, max. | see instruction list |
| • Size, max. | 64 kbyte |
| • Number of time alarm OBs | 2 |
| • Number of delay alarm OBs | 2 |
| • Number of cyclic interrupt OBs | 2 |
| • Number of process alarm OBs | 2 |
| • Number of multicomputing OBs | 1 |

Nesting depth

- | | |
|---------------------------------|----|
| • per priority class | 24 |
| • additional within an error OB | 1 |

Counters, timers and their retentivity

S7 counter

- | | |
|----------|-------|
| • Number | 2 048 |
|----------|-------|

Retentivity

- | | |
|---------------|------------|
| — adjustable | Yes |
| — lower limit | 0 |
| — upper limit | 2 047 |
| — preset | Z 0 to Z 7 |

Counting range	
— lower limit	0
— upper limit	999
S7 times	
• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	No times retentive
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
Data areas and their retentivity	
retentive data area in total	Total working and load memory (with backup battery)
Flag	
• Number, max.	4 kbyte
• Retentivity available	Yes; From MB 0 to MB 4095
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Local data	
• adjustable, max.	8 kbyte
• preset	4 kbyte
Address area	
I/O address area	
• Inputs	4 kbyte
• Outputs	4 kbyte
of which distributed	
— MPI/DP interface, inputs	2 kbyte
— MPI/DP interface, outputs	2 kbyte
— DP interface, inputs	4 kbyte; for each line that is operated in isochronous mode, i.e. to which an OB61 to 62 has been assigned, the distributed IO address areas are halved
— DP interface, outputs	4 kbyte; for each line that is operated in isochronous mode, i.e. to which an OB61 to 62 has been assigned, the distributed IO address areas are halved
Process image	
• Inputs, adjustable	4 kbyte
• Outputs, adjustable	4 kbyte

• Inputs, default	128 byte
• Outputs, default	128 byte
• consistent data, max.	244 byte
• Access to consistent data in process image	Yes
Subprocess images	
• Number of subprocess images, max.	15
Digital channels	
• Inputs	32 768
— of which central	32 768
• Outputs	32 768
— of which central	32 768
Analog channels	
• Inputs	2 048
— of which central	2 048
• Outputs	2 048
— of which central	2 048
Hardware configuration	
Number of expansion units, max.	21; of which 6 ER with K-bus
connectable OPs	15 without message processing, 8 with message processing
Multicomputing	Yes; 4 CPUs max. (with UR1 or UR2)
Interface modules	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	4; IM 463-2
Number of DP masters	
• integrated	2
• via CP	10; CP 443-5 Extended
• via IM 467	4
• Mixed mode IM + CP permitted	No; IM 467 cannot be used jointly with CP 443-5 Ext.
• via interface module	0
• Number of pluggable S5 modules (via adapter capsule in central device), max.	6
Number of operable FMs and CPs (recommended)	
• FM	Limited by number of slots and number of connections
• CP, PtP	CP 440: Limited by number of slots; CP 441: limited by number of connections
• CP, LAN	Limited by number of slots and number of connections
• PROFIBUS and Ethernet CPs	14; incl. CP 443-5 Ext. and IM 467
Slots	
• required slots	1
Time of day	

Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Resolution	1 ms
• Deviation per day (buffered), max.	1.7 s; Power off
• Deviation per day (unbuffered), max.	8.6 s; Power on
Operating hours counter	
• Number	8
• Number/Number range	0 to 7
• Range of values	0 to 32767 hours
• retentive	Yes
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes
1. Interface	
Interface type	Integrated
Physics	RS 485 / PROFIBUS
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	150 mA
Number of connection resources	MPI: 16, DP: 16
Functionality	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
MPI	
• Number of connections	16
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s

• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
DP slave	
• Number of connections	1
• GSD file	http://www.ad.siemens.de/csi_e/gsd
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— PG/OP communication	Yes
— Routing	Yes
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
2. Interface	
Interface type	Integrated
Physics	RS 485 / PROFIBUS
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	150 mA
Number of connection resources	16
Functionality	
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes

DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	64
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	
— Inputs, max.	4 kbyte
— Outputs, max.	4 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
DP slave	
• GSD file	http://www.ad.siemens.de/csi_e/gsd
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— Routing	Yes
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Equidistance	Yes
User data per isochronous slave, max.	244 byte
shortest clock pulse	1 ms
max. cycle	32 ms

Communication functions

PG/OP communication	Yes
<ul style="list-style-type: none"> • Number of connectable OPs without message processing 	15
<ul style="list-style-type: none"> • Number of connectable OPs with message processing 	8
Global data communication	
<ul style="list-style-type: none"> • supported 	Yes
<ul style="list-style-type: none"> • Number of GD loops, max. 	8
<ul style="list-style-type: none"> • Number of GD packets, transmitter, max. 	8
<ul style="list-style-type: none"> • Number of GD packets, receiver, max. 	16
<ul style="list-style-type: none"> • Size of GD packets, max. 	64 byte
<ul style="list-style-type: none"> • Size of GD packet (of which consistent), max. 	1 variable
S7 basic communication	
<ul style="list-style-type: none"> • supported 	Yes; in MPI mode via: SFC X_SEND, X_RCV, X_GET and X_PUT; in DP master mode via: SFC I_GET and I_PUT
<ul style="list-style-type: none"> • User data per job, max. 	76 byte
<ul style="list-style-type: none"> • User data per job (of which consistent), max. 	1 variable
S7 communication	
<ul style="list-style-type: none"> • supported 	Yes
<ul style="list-style-type: none"> • as server 	Yes
<ul style="list-style-type: none"> • as client 	Yes
<ul style="list-style-type: none"> • User data per job, max. 	64 kbyte
<ul style="list-style-type: none"> • User data per job (of which consistent), max. 	462 byte; 1 variable
S5 compatible communication	
<ul style="list-style-type: none"> • supported 	Yes; Via FC AG_SEND and AG_RECV, max. via 10 CP 443-1 or 443-5
<ul style="list-style-type: none"> • User data per job, max. 	8 kbyte
<ul style="list-style-type: none"> • User data per job (of which consistent), max. 	240 byte
Standard communication (FMS)	
<ul style="list-style-type: none"> • supported 	Yes; Via CP and loadable FB
Number of connections	
<ul style="list-style-type: none"> • overall 	16
<ul style="list-style-type: none"> • usable for PG communication <ul style="list-style-type: none"> — reserved for PG communication 	1
<ul style="list-style-type: none"> • usable for OP communication <ul style="list-style-type: none"> — reserved for OP communication 	1
S7 message functions	
Number of login stations for message functions, max.	8
Symbol-related messages	Yes
Program alarms	Yes
simultaneously active Alarm-S blocks, max.	70; ALARM_S/SQ blocks or ALARM_D/DQ blocks

Alarm 8-blocks	Yes
<ul style="list-style-type: none"> • Number of instances for alarm 8 and S7 communication blocks, max. 	300
<ul style="list-style-type: none"> • preset, max. 	150
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	4
Number of messages	
<ul style="list-style-type: none"> • overall, max. 	512
<ul style="list-style-type: none"> • in 100 ms grid, max. 	0
<ul style="list-style-type: none"> • in 500 ms grid, max. 	256
<ul style="list-style-type: none"> • in 1000 ms grid, max. 	256
Number of additional values	
<ul style="list-style-type: none"> • per message 	1
<ul style="list-style-type: none"> • with 100 ms grid, max. 	0
<ul style="list-style-type: none"> • with 500, 1000 ms grid, max. 	1
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	4
Status/control	
<ul style="list-style-type: none"> • Status/control variable 	Yes
<ul style="list-style-type: none"> • Variables 	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
<ul style="list-style-type: none"> • Number of variables, max. 	70
Forcing	
<ul style="list-style-type: none"> • Forcing 	Yes
<ul style="list-style-type: none"> • Forcing, variables 	Inputs/outputs, bit memories, distributed I/Os
<ul style="list-style-type: none"> • Number of variables, max. 	64
Diagnostic buffer	
<ul style="list-style-type: none"> • present 	Yes
<ul style="list-style-type: none"> • Number of entries, max. 	400
<ul style="list-style-type: none"> — adjustable 	Yes
<ul style="list-style-type: none"> — preset 	120
Configuration	
Configuration software	
<ul style="list-style-type: none"> • STEP 7 	Yes
Programming	
<ul style="list-style-type: none"> • Command set 	see instruction list
<ul style="list-style-type: none"> • Nesting levels 	8
<ul style="list-style-type: none"> • Access to consistent data in process image 	Yes
<ul style="list-style-type: none"> • System functions (SFC) 	see instruction list

• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Number of simultaneously active SFCs	
— DPSYC_FR	2
— D_ACT_DP	4
— RD_REC	8
— WR_REC	8
— WR_PARM	8
— PARM_MOD	1
— WR_DPARM	2
— DPNRM_DG	8
— RDSYSST	8; 1 to 8
— DP_TOPOL	1
Number of simultaneously active SFBs	
— RDREC	8
— WRREC	8
Know-how protection	
• User program protection/password protection	Yes
Dimensions	
Width	25 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	720 g
last modified:	03/16/2018