



Fuse-link, LV, 100 A, AC 500 V, BS88, 21 x 95 mm, gL/gG, BS

OSD100

General specifications		
Product name		Eaton Bussmann series low voltage british standard fuse
Part no.		OSD100
EAN		5027590505086
Product Length/Depth		95 millimetre
Product height		21 millimetre
Product width		21 millimetre
Product weight		55.75 gram
Compliances		RoHS Compliant
Product Tradename		None
Product Type		Low voltage british standard fuse
Product Sub Type		None
Electrical data		
Amperage Rating		100 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL
Product specifications		
Application		general industrial applications
Fuse type		OSD
Fitted with:		Offset bolted tags
Connection		74 mm Fixing Centre
Compatible fuse holder		
Suitable for		SC100 Safeclip fuse holder CM100F Red spot fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		Other
Type of current		AC
Rated voltage AC	V	500
Rated voltage DC	V	
Rated current	A	100
Utilization category		gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	8.5
Mounting holes		M5
Centre-to-centre distance of connections	mm	73.5